

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/087754 A1

(51) International Patent Classification⁷: **G01M 3/26**

(21) International Application Number: **PCT/NO03/00116**

(22) International Filing Date: **10 April 2003 (10.04.2003)**

(25) Filing Language: **Norwegian**

(26) Publication Language: **English**

(30) Priority Data:
20021726 12 April 2002 (12.04.2002) **NO**

(71) Applicant (for all designated States except US): **NATIONAL OILWELL NORWAY AS** [NO/NO]; Lagerv. 8, N-4033 Stavanger (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KYLLINGSTAD, Åge** [NO/NO]; Barkv. 14, N-4330 Ålgård (NO).

(74) Agent: **HÅMSØ PATENTBYRÅ ANS**; P.O. Box 171, N-4302 Sandnes (NO).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD AND DEVICE FOR DETECTING LEAKS IN RECIPROCATING MACHINERY**



(57) Abstract: A method of and device for detecting a leak in reciprocating machinery (1), comprising at least two pistons (2, 2'), by the volume flow at least out of the reciprocating machinery (1) being monitored and analysed, e.g. by means of Fourier analysis, in order to make it possible to detect a flow component, where the flow component has a frequency that differs from the fundamental frequency of the reciprocating machinery, the fundamental frequency of the reciprocating machinery being constituted by the rotational frequency of the reciprocating machinery multiplied by the number of pistons (2, 2') in the reciprocating machinery.



WO 03/087754 A1

METHOD AND DEVICE FOR DETECTING LEAKS IN RECIPROCATING
MACHINERY

This invention regards a method of detecting a leak in a piece of reciprocating machinery. The method may also be used
5 for localising a leak. In this context, reciprocating machinery means all types of pumps and hydraulic machineries that are equipped with a rotating crankshaft or cam, where the crankshaft or cam drives or is driven by at least two pistons in a controlled reciprocating motion, and where each
10 piston cylinder is provided with at least two check valves designed to rectify the direction of flow through the machine. The invention also comprises a device for implementing the method.

When operating reciprocating machinery, safety considerations
15 and economics make it very important to detect leaks in e.g. piston seals and valves at an early stage. Leaks of this type are acceleratory, and when they become large enough for the operator of the reciprocating machinery to detect them through large abnormal pressure variations, the reciprocating

machinery must often be shut down and overhauled immediately and without the option of postponing the maintenance work to a later and operationally more suitable time.

The object of the invention is to present a method of
5 detecting an incipient leak before it reaches an extent that interferes with the operation, whereby repairs may be scheduled for a later point of time.

The object is achieved in accordance with the invention by the characteristics given in the description below and in the
10 appended claims.

The method comprises an analysis of the flow rate into and out of the reciprocating machinery in order to detect a new flow rate component, where the flow rate component has a frequency that differs from the fundamental frequency of the
15 reciprocating machinery. Fundamental frequency is here taken to mean the rotational frequency of the reciprocating machinery multiplied by the number of pistons in the machine. The flow rates may be estimates based on pressure measurements.

20 Ideally, the flow rates into and out of the reciprocating machinery should be as steady as possible, but in practice the flow rates, and consequently the pressure, will fluctuate in correlation with the speed of rotation of the machinery. Such fluctuations are principally caused by geometric factors
25 that cause the sum of the piston speeds in each phase not to be constant, the compressibility of the fluid which makes it necessary to compress and then decompress the fluid prior to equalising the pressure and opening the respective valves,

valve inertia that cause further delays in the opening and closing of valves, and flow-dependent pressure drop through valves and feed passages. If all pistons and valves are identical and operate normally, the fluctuations will as a result of symmetry have a fundamental frequency equal to the rotational frequency of the machinery multiplied by the number of pistons in the machine. However, if an abnormal leak were to occur in e.g. one of the pistons or one of the valves, the symmetry would be broken and the fluctuations in the flow would have new frequency components, with the lowest frequency equal to the rotational frequency of the machine.

The angular position θ of the rotating crankshaft or cam of the reciprocating machinery is measured directly or indirectly and normalised to values of between 0 and 2π , optionally between $-\pi$ and π radians, where 0 represents the start of the power stroke of piston no. 1. The reciprocating machinery comprises two or more pistons uniformly distributed, so that piston no. i of a total of n pistons has a phase lag (angle) of $(i-1)2\pi/n$ relative to the first piston.

The pressure into or out of the machinery is measured, whereupon the measured pressure signals are transformed into functions representing normalised flow rates into and out of the machinery. This means that if, for instance, q_{in} and q_{av} represent instantaneous and average flow rates into the reciprocating machinery, the normalised inflow function is defined so that

$$f/(p_{in}) \approx q_{in}/q_{av}.$$

It is well known to those skilled in the art that a periodic signal can be split up into components of different frequencies, e.g. by use of Fourier analysis. The i^{th} harmonic component of the reciprocating machinery frequency may be
5 represented by two coefficients defined by the following integrals:

$$s_i = \frac{1}{\pi} \int_0^{2\pi} f \sin(i\theta) d\theta \quad (1)$$

$$c_i = \frac{1}{\pi} \int_0^{2\pi} f \cos(i\theta) d\theta \quad (2)$$

These integrals, which in practice must be implemented as
10 summations in a computer or in a programmable logic controller (PLC), are updated for each new revolution of the reciprocating machinery. If the function f is purely periodic with the pump angle, the integrals will be constant. However, f can often contain significant non-periodic components
15 caused by e.g. a change in the pump speed or a variation in the external flow resistance. The non-periodic components may be regarded as stochastic noise, and may consequently be suppressed relative to the periodic components by use of known smoothing or averaging techniques. As an example,
20 recursive smoothing can be applied according to the recipe

$$a_i(k) = (1-x)a_i(k-1) + xs_i(k) \quad (3)$$

$$b_i(k) = (1-x)b_i(k-1) + xc_i(k) \quad (4)$$

where the argument refers to the estimate following revolution number k of the machinery, and x is a positive weighting function that is normally much smaller than 1. This smoothing filter, which is a low-pass filter of the first order, allows all the previous estimates of sine and cosine coefficients to form part of the estimated resultant coefficients, but with the weighting decreasing exponentially backwards in time. If the non-periodic variations are relatively large, it may be necessary to use a second-order smoothing and/or select an even smaller weighting function x .

The amplitude of the first harmonic frequency component:

$$f_1 = \sqrt{a_1^2 + b_1^2} \quad (5)$$

represents a quantitative measure of the leakage in the machinery. In the event of a small leak, this component will start to increase from its low normal noise level long before the leak becomes large enough for the associated pressure fluctuation to show up directly on a manometer or in a graph of the pressure signals.

The method is also well suited for locating the main source of the leak. This is possible because the Fourier analysis contains phase information through the two frequency components a_1 and b_1 . The connection between the frequency components may through use of a well known trigonometric identity be expressed as

$$a_1 \sin(\theta) + b_1 \cos(\theta) = f_1 \sin(\theta - \varphi) \quad (6)$$

where

$$\tan(\varphi_1) = a_1/b_1 \quad (7)$$

The sign of the coefficient determines in which quadrant the angle φ_1 lies.

- 5 Each type of leak has its own signature, as explained in some of the following examples. The functions f and g represent functions that are approximately proportional to the incoming and outgoing volumetric flow rates respectively. This means that the associated phase angles φ_1 and γ_1 are direct
10 expressions of the first harmonic component of the maxima of the fluid flows.

The following describes several non-limiting examples of use of the method illustrated in the accompanying drawings, in which:

- 15 Figure 1 schematically shows a triplex pump equipped with the required measuring devices and analysers; and

Figure 2 shows a curve illustrating the delivered volumetric flow as a function of the rotational angle of the pump, showing the central point of a piston leak.

- 20 In the drawings, reference number 1 denotes a so-called triplex pump equipped with three individually acting pistons 2, 2' and 2'' respectively, of which only piston 2 is shown, extending through their respective cylinders 4, 4' and 4''. The cylinders 4, 4' and 4'' communicate with an inlet manifold

6 through their respective inlet valves 8, 8' and 8'', and an outlet manifold 10 through their respective outlet valves 12, 12' and 12'', respectively. An inlet pressure sensor 14 is connected to the inlet manifold 6, communicating with a computer 16 via a line 18, and an outlet pressure sensor 20 is connected to the outlet manifold 10, communicating with the computer 16 via a line 22. A rotational angle transmitter 24 is designed to measure the rotational angle of the crankshaft 26 of the pump 1, and is communicatively connected to the computer 16 by means of a line 28. The sensors 14 and 20, the transmitter 24 and the computer 16 are of types that are known *per se*, and the computer is programmed to carry out the calculations concerned.

In the event of a leak in the seal of the first piston 2, the outflow through the outlet valve 12 is reduced during the pumping phase by a quantity equal to the leakage past the piston 2. As the pump stroke extends over half a revolution of the crankshaft 26 of the pump 1, the central point 32, see figure 2, for this reduction in volume flow is approximately $\pi/2$ radians (90°) after the start of the pump stroke. In figure 2, the curve 34 indicates the reduction in the average volume flow 36 which occurs as a result of the piston leakage. In reality, the central point 32 will lag by an additional, small angle. This is due to both compression and decompression of the pumped fluid, and the fact that with a crank drive, where the crankshaft (not shown) of the piston 2 has a finite length, the maximum piston speed is reached only at approximately 100° . These effects may be calculated and compensated for by adding a pressure and geometry dependent phase lag δ . The corresponding angle γ_1 on the first harmonic component of the outflow function g will therefore be shifted

by half a revolution relative to that point, i.e. to $\gamma_1 = -\pi/2 + \delta$. Due to the fact that the pressure during the return or suction stroke of the piston 2 is far lower, the inflow rate, and consequently also the function f , will be relatively
5 unaffected by a piston leak, whereby $f_1 \approx 0$.

The above example may easily be generalised to a rule which states that in the event of a leak in piston number i of a total of n pistons with a mutual displacement of phases of $2\pi/n$, then

10
$$f_1 \approx 0 \quad (8)$$

$$g_1 > 0 \quad (9)$$

$$\gamma_1 = -\pi/2 + \delta + 2(i-1)\pi/n \quad (10)$$

The inequality > 0 here indicates that g_1 must be interpreted as being significantly greater than the level of background
15 noise.

If the leak is in the inlet valve 8 instead of in the piston 2, the effect on the out function will be the same as in the case of a pure piston leak. However the drop in the outflow will now be balanced by a similarly negative inflow. It can
20 therefore be concluded that in the event of a leak in in-valve number i , (9) and (10) will still apply, but (8) must be replaced by

$$f_1 > 0 \quad (11)$$

$$\varphi_1 = \gamma_1 = -\pi/2 + \delta + 2(i-1)\pi/n \quad (12)$$

A leak in outlet valve 12 will lead to a reduction in both the inflow and the outflow during the return phase. Then both (11) and (9) will apply, but the phase angle is displaced by half a revolution, to

$$\varphi_1 = \gamma_1 = \pi/2 + \delta + 2(i-1)\pi/n \quad (13)$$

In those cases where n is an odd number, the source of the leakage will be determined uniquely. The reason for this is that the phase angles defined by equation (12) are all different from the phase angles defined by equation (13). However, if the number of pistons is an even number, the leakage determination will be two-valued, at least if the leak is in one of the valves. The reason for this is that a leak in an inlet valve number i will have the same signature as a leak in the complementary out valve (number $i \pm n/2$) and vice versa.

C l a i m s

1. A method of detecting a leak in reciprocating machinery (1), comprising at least two pistons (2, 2'),
c h a r a c t e r i z e d i n that the volume
5 flow at least out of the reciprocating machinery (1) is monitored and analysed, e.g. by means of Fourier analysis, in order to make it possible to detect a flow component, where the flow component has a frequency that differs from the fundamental frequency of the
10 reciprocating machinery, the fundamental frequency of the reciprocating machinery being constituted by the rotational frequency of the reciprocating machinery multiplied by the number of pistons (2, 2') in the reciprocating machinery.
- 15 2. A method in accordance with Claim 1,
c h a r a c t e r i z e d i n that the volume flow into and/or out of the reciprocating machinery (1) is monitored, and a flow component is compared with information regarding the shaft/cam angle of the
20 reciprocating machinery (1) in order to allow localisation of the leak associated with the flow frequency component in question, through knowledge of the relationship between the flow frequency component and the shaft/cam angle of the reciprocating pump.
- 25 3. A device for detecting a leak in reciprocating machinery (1), comprising at least two pistons (2, 2'),
c h a r a c t e r i z e d i n that the reciprocating machinery (1) is provided with at least one measuring device (14, 16) designed to give a direct

or indirect measurement of a volume flow through the reciprocating machinery (1), the measuring device (14, 16) being connected to a computer that is programmed to separate out flow components having a frequency that differs from the fundamental frequency of the reciprocating machinery.

4. A device in accordance with Claim 3, characterized in that the reciprocating machinery (1) is provided with a rotational angle transmitter (24) connected to the computer (16), which transmitter is designed to measure the shaft/cam angle of the reciprocating machinery (1) in order to allow localisation of the leak associated with the flow frequency component in question, through knowledge of the relationship between the flow frequency component and the shaft/cam angle of the reciprocating pump (1).

1/2





Fig. 1

2/2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 03/00116

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G01M 3/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5471400 A (SMALLEY ET AL), 28 November 1995 (28.11.95), abstract --	
A	US 5203822 A (GÜRICH ET AL), 20 April 1993 (20.04.93), abstract -- -----	

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 June 2003

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Date of mailing of the international patent search report

18-06-2003

Authorized officer

Dan Ionesco / JA A
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

29/04/03

International application No.

PCT/NO 03/00116

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	5471400	A	28/11/95	NONE	
US	5203822	A	20/04/93	DE 4011422 A,C FR 2660753 A,B	10/10/91 11/10/91